

INTRODUCTION OF THE 76 MM (3") ADVANCED™ SERIES PRO-FLO X™ BRAHMA PUMP

Wilden® is excited to announce the new 76mm (3") center-ported Advanced™ Series Pro-Flo X™ Brahma pump. PX1510 Brahma pumps feature a flanged 76mm (3") top inlet and bottom discharge. Additionally, the Brahma flow path uses flap valves for maximum solids passage. These features avoid damage from product entrapment and settling solids in intermittent-duty applications.

This new Advanced™ Brahma™ pump comes equipped with the patented Pro-Flo X Air Distribution System (ADS), featuring the Efficiency Management System (EMS). The EMS optimizes the operation of the Brahma pump with the turn of an integrated control dial. This enables the pump user to select the desired efficiency point and flow rate that best suits the application. The results are higher performance, lower operational costs and performance flexibility.

Brahma pumps can be ordered with aluminum or ductile iron wetted materials and buna-N or neoprene elastomers for the most demanding applications.

Features & Benefits

- Pump list prices set to match current Pro-Flo V™ Brahma pumps
- DIN or ANSI connections
- Top inlet and bottom discharge
- Aluminum or ductile iron wetted path
- Flap valves for maximum solids passage
- Pro-Flo X™ ADS with EMS™
- Single point exhaust option
- Max. operating pressure 8.6 bar (125 psig)
- Maximum flow rate of 958 lpm (253 gpm)
- Optional anodized aluminum air valve and air valve spool for severe service



airpumping.co.uk

est. 1979

Unit 16, Uppminster Trading Park, Warley St, Uppminster, Essex, RM14 3PJ, ENGLAND

22069 Van Buren Street, Grand Terrace, CA 92313
Tel 909.422.1730 • Fax 909.783.3440

www.wildenpump.com