

INTRODUCTION OF THE POLYPROPYLENE PRO-FLO X™ AIR DISTRIBUTION SYSTEM FOR ORIGINAL™ SERIES PUMPS

Wilden is excited to announce unparalleled performance for plastic Air Distribution Systems (ADS) with the availability of the polypropylene Pro-Flo X™ for Original™ series pumps. The Pro-Flo X™ ADS is now capable of withstanding the most aggressive chemical applications where aluminum and nickel-plated aluminum Pro-Flo X™ ADS components are unsuitable. This new ADS offering fits existing polypropylene and PVDF Original™ series pump models in the 38 mm (1-1/2") size and existing polypropylene models in the 51 mm (2") size.

The patent pending plastic Pro-Flo X™ ADS with Efficiency Management System (EMS™) offers increased performance, long-lasting chemically resistant polypropylene construction, and the same reliable operation as existing Pro-Flo® and Pro-FloX™ metal ADS you've come to trust. The plastic Pro-Flo X™ ADS features a common air valve assembly for both pump sizes, which allows distributors and end users alike to carry reduced inventory for service and repairs.

Design Features:

- Efficiency Management System (EMS™)
- Lube-free operation
- Superior anti-freezing performance
- Maximum air inlet temperature 82 °C (180 °F)
- Maximum operating pressure 8.6 bar (125 psig)
- Available in Original™ series pumps
- Sizes available: 38 mm (1-1/2"), 51 mm (2")

Pricing Considerations:

- Same price as Pro-FloX™ Aluminum ADS



22069 Van Buren Street, Grand Terrace, CA 92313
Tel 909.422.1730 • Fax 909.783.3440

www.wildenpump.com

WILDEN
A DOVER COMPANY