

INTRODUCTION OF THE PRO-FLO X™ STALLION® ORIGINAL™ SERIES PUMPS

Wilden is proud to announce the addition of the Pro-Flo X™ air distribution system (ADS) to the Stallion® line of pumps in the 38 mm (1-1/2"), 51 mm (2"), and 76 mm (3") sizes. The revolutionary Pro-Flo X™ ADS can now be used in the most demanding applications where the Stallion® line excels. The patent pending Pro-Flo X™ ADS fits into the existing Stallion® Original™ Series wetted path.

The new Pro-Flo X™ Stallion® ADS features an anodized aluminum air valve body and air valve spool to withstand unfiltered and particle-laden air. Pro-Flo X™ Stallion® models will be configured with the single-point-exhaust option for submerged operation.

Features, Benefits and Details:

- Efficiency Management System (EMS™)
- Lube-free operation
- Anodized aluminum air valve and air valve spool
- Single-point-exhaust
- Ultra-Flex™ elastomers for long life, maximum solids passage and maximum MTBR
- Maximum air inlet temperature 88 °C (180 °F)
- Maximum operating pressure 8.6 bar (125 psig)
- Sizes available: 38 mm (1-1/2"), 51 mm (2") and 76 mm (3")
- Maximum solids passage:
 - PX4 Stallion = 13mm (1/2")
 - PX8 Stallion = 19mm (3/4")
 - PX15 Stallion = 25mm (1")



22069 Van Buren Street, Grand Terrace, CA 92313
Tel 909.422.1730 • Fax 909.783.3440

www.wildenpump.com

WILDEN
A DOVER COMPANY